









# STEEL WHEELS

EMAIL: SALES@POLONEZINDUSTRIES.COM WECHAT/WHATSAPP:+86-18605327632 WWW.POLONEZINDUSTRIES.COM

Please contact us promptly for more new specifications

Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	PHOTO
	Hole DIA(mm)	Number	Nut Type						
19.5×6.00	29/32	5	1*45°	203.5	146	115	225/70R19.5	360	
19.5×6.00	32.5	5	SR22	208	150	120			
19.5×6.00	20.5/21.5	6	SR16/SR18/1*45°	190	140	115			
19.5×6.00	20.5/21.5	6	1*45°	205	161	125			
19.5×6.00	32.5	6	SR22	222.25	164	135			
19.5×6.00	21.5	6	SR16	245	202	135			
19.5×6.00	26/21.5/24.5/25.4	8	SR16/SR18/1*45°	275	221	134			
19.5×6.00	26	10	1*45°	225	176	133			
19.5×6.00	26/32	5	SR16/SR18/1*45°	205	161	125			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
Hole DIA(mm)	Number	Nut Type							
19.5×6.75	32.5	6	1*45°/SR22	203.2	146	115	245/70R19.5	360	
19.5×6.75	32	8	SR22	208	150	120			
19.5×6.75	26/21.5/24.5/25.4	8	1*45°/SR22	190	140	108			
19.5×6.75	21.5	8	1*45°	205	161	125			
19.5×6.75	26/21.5	10	SR22	222.25	164	135			
19.5×6.75	24.5	10	SR16/1*45°	245	202	135			
19.5×6.75	21	10	1*45°/SR22/SR18	205	161	125			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
Hole DIA(mm)	Number	Nut Type							
19.50×7.50	32.5/26	5	1*45°/SR22/SR18	205	164	145	265/70R19.5	360	
19.50×7.50	32.5	8	SR22	275	214	145			
19.50×7.50	26/21.5/24.5/25.4	8	SR16/SR18/1*45°	275	221	135			
19.50×7.50	32.5	8	SR22	285	221	145			
19.50×7.50	26	10	1*45°	285.75	220	145			
19.50×7.50	26/21.5	10	SR16/SR18/1*45°	176	225	135			
19.50×7.50	20.5/21.5	6	SR16/1*45°	205	164	145			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
Hole DIA(mm)	Number	Nut Type							
19.5×8.25	32.5	5	SR22	205	161	0	285/70R19.5	360	
19.5×8.25	21.5	8	SR16/1*45°	275	221	66			
19.5×8.25	25.4/24.5	8	SR18/1*45°	275	221	0			
19.5×8.25	26	8	SR18/1*45°	275	221	146			
19.5×8.25	32.5	8	SR22	285	221	153.5			
19.5×8.25	21	10	SR16/1*45°	225	176	146.5			
19.5×8.25	26	10	SR18/1*45°	225	176	0			
19.5×8.25	26	10	1*45°	285.75	220	146.5			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
Hole DIA(mm)	Number	Nut Type							
19.5×14.00	21.5/24.5	8	SR16/1*45°	275	221	0	425/55R19.5 445/45R19.5 445/65R19.5	280	
19.5×14.00	25.4/26	8	SR18/1*45°	275	221	120			
19.5×14.00	26	10	1*45°	285.75	220	0			
19.5×14.00	26	10	1*45°	335	281	0			
19.5×14.00	27	10	SR18	335	281	120			
19.5×14.00	20.5/21.5	6	SR16/1*45°	205	161	0			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
Hole DIA(mm)	Number	Nut Type							
22.5×6.00	32.5	6	SR22	222.25	164	135	9R22.5	360	
22.5×6.00	20.5	6	SR16/SR22/1*45°	190	140	135			
22.5×6.00	21.5	6	SR16	245	202	138			
22.5×6.00	32.5	8	SR22	275	214	140			
22.5×6.00	32.5	8	SR22	285	221	135			
22.5×6.00	26/21.5	10	SR16/SR18/1*45°	225	176	130			

Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×6.75	32	8	SR22	275	214	152	9R22.5 10R22.5 255/70R22.5	360	
22.5×6.75	32	8	SR22	285	221	140			
22.5×6.75	26/21.5/24.5/25.4	8	SR16/SR18/1*45°	275	221	140			
22.5×6.75	32	10	SR22	285.75	222	140.5			
22.5×6.75	26	10	1*45	335	281	142			
22.5×6.75	27	10	SR18	335	281	142			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×7.50	32	8	SR22	275	214	152	10R22.5 11R22.5 255/70R22.5 265/60R22.5 275/70R22.5 275/80R22.5	320	
22.5×7.50	32	8	SR22	285	221	165			
22.5×7.50	26/21.5/24.5/25.4	8	SR16/SR18/1*45°	275	221	158			
22.5×7.50	32	10	SR22	285.75	222	165			
22.5×7.50	26	10	1*45	335	281	152			
22.5×7.50	27	10	SR18	335	281	152			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×8.25	32	8	SR22	275	214	169	11R22.5 12R22.5 255/70R22.5 265/60R22.5 275/70R22.5 275/80R22.5	280	
22.5×8.25	32	8	SR22	285	221	165			
22.5×8.25	26	8	1*45	275	221	165			
22.5×8.25	26	10	1*45	285.75	220	165			
22.5×8.25	32	10	SR22	285.75	222	169			
22.5×8.25	27	10	SR18	335	281	169			
22.5×8.25	26	10	1*45	335	281	169			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×9.00	32	8	SR22	275	214	175	12R22.5 13R22.5 295/75R22.5 295/80R22.5 315/60R22.5 315/70R22.5 315/80R22.5	280	
22.5×9.00	32	8	SR22	285	221	175			
22.5×9.00	26	8	1*45	275	221	175			
22.5×9.00	26	10	1*45	285.75	220	175			
22.5×9.00	32	10	SR22	285.75	222	175			
22.5×9.00	27	10	SR18	335	281	175			
22.5×9.00	26	10	1*45	335	281	175			
22.5×9.00	26	10	1*45	335	281	175			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×11.75	21.5/24.5/25.4	8	SR16/1*45°	275	221	0	385/55R22.5 385/65R22.5	240	
22.5×11.75	26	8	SR18/1*45°	275	221	120			
22.5×11.75	26	10	1*45	335	281	120			
22.5×11.75	27	10	SR18	335	281	0			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×14.00	21.5	8	SR16/1*45°	275	221	0	425/65R22.5 445/65R22.5 445/50R22.5	200	
22.5×14.00	26	8	SR18/1*45°	275	221	0			
22.5×14.00	32	10	SR22	285.75	222	60			
22.5×14.00	26	10	1*45°	285.75	220	75			
22.5×14.00	26	10	1*45°	335	281	120			
22.5×14.00	27	10	SR18	335	281	0			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
22.5×16.00	21.5	8	SR16/1*45°	275	221	0	455/40R22.5	200	
22.5×16.00	26	8	SR18/1*45°	275	221	0			
22.5×16.00	32	10	SR22	285.75	222	60			
22.5×16.00	26	10	1*45°	285.75	220	75			
22.5×16.00	26	10	1*45°	335	281	120			
22.5×16.00	27	10	SR18	335	281	0			

Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
17.50×5.25	29/32	5	1*45°/SR22	203.2	146	115	8R17.5 8.5R17.5 205/75R17.5	450	
17.50×5.25	32.5	5	SR22	208	150	120			
17.50×5.25	20.5/21	6	1*45°/SR22	190	140	108			
17.50×5.25	20.5/21	6	1*45°	205	161	125			
17.50×5.25	32.5	6	SR22	222.25	164	135			
17.50×5.25	21.5	6	SR16/1*45°	245	202	135			
17.50×5.25	26/32	5	1*45°/SR22/SR18	205	161	125			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
17.50×6.00	29/32	5	1*45°/SR22	203.2	146	115	205/65R17.5 205/75R17.5 215R/7517.5 225/70R17.5 225/75R17.5 8R17.5 8.5R17.5 9.5R17.5	450	
17.50×6.00	32.5	5	SR22	208	150	120			
17.50×6.00	20.5/21.5	6	SR16/SR22/1*45°	190	140	115			
17.50×6.00	20.5/21.5	6	1*45°	205	161	125			
17.50×6.00	32.5	6	SR22	222.25	164	135			
17.50×6.00	21.5	6	SR16/1*45°	245	202	135			
17.50×6.00	26/21.5/25.4/24.5	8	1*45°/SR18/SR16	275	221	134			
17.50×6.00	26/21.5	10	1*45°/SR18/SR16	225	176	133			
17.50×6.00	26/32	5	SR18/SR22/1*45°	205	161	125			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
17.50×6.75	29/32	5	1*45°/SR22	203.2	146	115	205/65R17.5 205/75R17.5 215/75R17.5 225/70R17.5 225/75R17.5 235/75R17.5 245/70R17.5 245/75R17.5 265/70R17.5	450	
17.50×6.75	32.5	5	SR22	208	150	120			
17.50×6.75	20.5/21.5	6	SR16/SR22/1*45°	190	140	115			
17.50×6.75	20.5/21.5	6	1*45°	205	161	125			
17.50×6.75	32.5	6	SR22	222.25	164	135			
17.50×6.75	21.5	6	SR16	245	202	135			
17.50×6.75	26/21.5/24.5/25.4	8	SR16/SR18/1*45°	275	221	134			
17.50×6.75	26/21.5	10	SR16/SR18/1*45°	225	176	133			
17.50×6.75	26/32	5	SR16/SR22/1*45°	205	161	125			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
24.5×8.25	32	8	SR22	275	214	169	11R24.5 285/75R24.5	208	
24.5×8.25	32	8	SR22	285	221	165			
24.5×8.25	26	8	1*45°/SR18	275	221	165			
24.5×8.25	26	10	1*45°	285.75	220	165			
24.5×8.25	32	10	SR22	285.75	222	169			
24.5×8.25	27	10	SR18	335	281	169			
24.5×8.25	26	10	1*45°	335	281	169			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
8.50-24	27	10	1*45°/SR18/SR22	335	281	180	12.00R24 325/95R24	208	
8.50-24	32.5	8	SR22	285	221	180			
8.50-24	32.5	10	SR22	285.75	222	180			
8.50-24	26	10	1*45°	285.75	220	180			
8.50-24	24.5	8	1*45°	275	221	175			
8.50-24	21.5	8	SR16	275	221	175			
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP	
	Hole DIA(mm)	Number	Nut Type						
8.50-20	26	10	1*45°/SR18	335	281	180	11.00R20 12.00R20	320	
8.50-20	32	8	SR22	285	221	180			
8.50-20	26	10	1*45°	285.75	220	180			
8.50-20	32	10	SR22	285.75	222	180			
8.50-20	26	8	1*45°	275	221	180			

Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP
	Hole DIA(mm)	Number	Nut Type					
7.50-20	32	8	SR22	285	221	165	10.00R20 11.00R20	320
7.50-20	26	10	1*45°	285.75	220	165		
7.50-20	26	10	1*45°/SR18	335	281	165		
7.50-20	32	10	SR22	285.75	222	165		
7.00-20	32	8	SR22	275	214	152	825R20 9.00R20	320
7.00-20	26	10	1*45°	285.75	220	152		
7.00-20	32	10	SR22	285.75	222	152		
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP
	Hole DIA(mm)	Number	Nut Type					
6.5-16	32	6	1*45°	222.5	164	130	8.25R16	780
6.5-16	32	6	SR22	190	164	130		
6.5-16	20.5	6	1*45°/SR22	203.2	140	130		
6.5-16	20.5/21	6	1*45°/SR22	205	161	130		
6.5-16	24.5	8	SR22	205	161	125		
6.5-16	26	10	1*45°	225	176	137.5		
6.5-16	20.5	5	SR22	208	140	125		
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP
	Hole DIA(mm)	Number	Nut Type					
6.00G-16	32	6	SR22	222.25	164	123	750R16 8.25R16	845
6.00G-16	20.5	6	SR22	190	140	125		
6.00G-16	18	6	1*45°	205	161	125		
6.00G-16	32	6	SR22	203.2	140	125		
6.00G-16	32	5	SR22	208	150	115		
Wheel size	Bolt Hole			P.C.D (mm)	Center Bore DIA (mm)	Offset (mm)	Permitted Tires	QTY/20GP
	Hole DIA(mm)	Number	Nut Type					
5.5F-16	32	6	SR22	222.25	164	104	700R16 750R16	845
5.5F-16	32.5	6	SR22	222.25	164	113		
5.5F-16	20.5	6	SR22	190	140	115		
5.5F-16	29	5	SR22	203.2	146	108		
5.5F-16	32.5	5	SR22	208	150	115		
5.5F-16	32.5	5	SR22	203.2	146	108		
5.5F-16	32.5	5	SR22	203.2	146	112		

